


AP-115

Aprestine®

WHITE LABEL

Refurbishing plaster suitable for covering laminated stucco and for renewing rough, full of holes or embossed surfaces.



* information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions).

INDOOR



USE

Gypsum, plaster, cement, prefabs., non-elastic synthetic paint.
Surfaces must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Slow drying.
- Easy to apply, smooth and sand.
- Non-repellent.
- Applicable in thin layer.
- Smooth and fine finish.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Smoothing walls with small flaws.
- * High quality smoothing of large layering.
- * Fine coat covering of plastered refurbishing.



COATED

BY ALL KINDS OF CONVENTIONAL NON- RESILIENT
PAINTS AFTER COMPLETE DRYING

CLASSIFICATION ACCORDING TO
UNE 48313: 2008 EX

G3E5S2V3W2A0C0



Pallet of 66 sacks
x 15 Kgs.



Pallet of 35 cases
of 4 x 5 Kgs



PREPARATION

0.40 to 0.45 litres of water per Kg. of plaster



PERFORMANCE

1.65-1.80 Kg/m²/mm



MAXIMUM THICKNESS PER COAT

1 mm



ADHESION

>6kg/cm² on cement and paint



6.0-7.0



FIRE RESISTANCE CLASSIFICATION

A1



USEFUL LIFE

8 Hrs. approx



DRYING TIME

Plaster: 6 - 7 hrs
Concrete and paint: 8 hrs.approx.



MAXIMUM GRADING

300 microns