

B-18

B-18C

CRACK FILLER

Product indicated to fill and cover small holes, scratches, knocks, cracks, microcracks and static cracks.



INTERIOR



INFORMATION ABOUT DIRECTIVE 2004/42/CE

CATEGORY I1, HIGH PERFORMANCE COMPONENT COATINGS, WATERBASED

Limit: 140 g/l VOC (2007); 140 g/l VOC (2010)

This product contains max. 6,90 g/l VOC

SURFACES

Plaster, plaster of Paris, cement, non-elastic plastic paint, plasticised plaster and fibreglass. Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Excellent workability
- Easy to smooth and sand.
- Does not come adrift.
- High coverage power.
- It can be coated with all common types of paints after it has dried completely.
- Storage: 12 months in its original packaging and protected from moisture.

IDEAL FOR

- Repairing scratches, knocks and microcracks.



Pallet of 120 boxes
of 12 x 200 g



Pallet of 120 boxes
of 12 x 310 ml



Preparation
Ready to use



Performance
0,55 m²



9.0 - 10.0



Maximum thickness per layer
1 mm



Adherence
> 8 Kg/cm² on concrete and paint



Fire classification
A2 - s1 - d0



Use time
No limits



Drying in 1 mm thickness
Cement and paint: 6 - 7 H



Maximun granulometry
< 50 microns



BAIXENS ESPAÑA
POL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE
14, RUE DU PONT NEUF
75001 PARIS (FRANCE)
T.: 0.800.90.14.37
F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
VIA PIETRO NENNI, 36
46019 CICOGNARA - MANTOVA (ITALY)
T.: 0375/88181/790016 F.: 0375/88831
www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
AVENIDA PORTAS DO MINHO, Nº 711
4760 - 706 RIBEIRÃO,
V.N. FAMILICÃO
T.: 252 910 030 | www.argatintas.pt

B18NF256A20 / B18CNF1222A20