

B-22C

CARTRIDGES

UNIVERSAL ADHESIVE

Product suitable for gluing and pasting any type of material.









INFORMATION OF DIRECTIVE 2004/42/CE CATEGORY 11, HIGH PERFORMANCE WATERBASED COATINGS OF ONE COMPONENT

LIMIT: 140G/L/COV (2007); 140 G/L COV (2010) THIS PRODUCT CONTAINS 4,92 G/L COV MAX.

USES

Moulds, rosettes, ceiling lamps, skirting boards, frames, gypsum, brick, wood, plastic, ceramics, cork and polystyrene.

Substrates must be healthy, dry, cohesive, absorbent, well adhered and be absorbent on one part at least.

FEATURES

- Solid and permanent fastening.
- Excellent adherence and elasticity.
- Easy to apply.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

 Gluing wood, parquet, polystyrene, earthenware, ceramics and any type of product of absorbent surface.



Palet de 120 cajas de 12 x 310 ml



Preparation Ready to use.



Performance 0,75 m²/kg



7.0 - 8.0



Espesor máximo por capa



Maximum granulometry 200 microns



Fire classification D - s2 - d0





Drying in 1mm thickness 4 – 5 hrs.