

B-25C

CARTRIDGES

ADHESIVE FOR TILES

Product suitable for fast and practical placement of tiles and pieces of ceramic.



USES

Gypsum, plaster, cementitious, absorbent bases in general.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of applying on tiles.
- White colour.
- Flexible product.
- Storage: 12 months inside its original packing stored away from damp and humidity.

IDEAL FOR

- Placing of tiles in the interior independent to their grade of absorption and format.
- Placing and pasting of decorative borders, splines and ceramic and stone tile studs.



INFORMATION OF DIRECTIVE 2004/42/CE

CATEGORY I1, HIGH PERFORMANCE WATER-BASED COATINGS OF ONE COMPONENT

LIMIT: 140G/L/COV (2007); 140 G/L COV (2010)
THIS PRODUCT CONTAINS 13,88 G/L COV MAX.



Pallet of 120 cases
of 12 x 310 ml



Preparation
Ready to use.



Performance
3 - 3.5 Kg/m²



Fire classification
A2 - s1 - d0



Maximum time for correcting tile
50 - 60 mins.



Open time
45 - 70 mins. on concrete.



Cleansing of tools
Use water