







# PLASTIC FIBRE PASTE

Product designed to repair microfissures and stubborn cracks.





EXTERIOR INTERIOR

**SURFACES** 

Plaster, plaster of Paris, cement, brick, stone, wood, concrete, aerated concrete, semiabsorbent surfaces.

Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

## **CHARACTERISTICS**

- Reinforced with fibreglass.
- Extra white.
- Applicable in thick layers.
- Excellent thixotropy.
- Highly flexible.
- High adherence.
- Storage: 12 months in its original packaging and protected from moisture.

### **IDEAL FOR**

- Covering and repairing static and dynamic cracks.
- Filling small holes.
- Replacing fibreglass bands.



#### **INFORMATION ABOUT DIRECTIVE 2004/42/CE**

CATEGORY i1, HIGH PERFORMANCE COMPONENT COATINGS, WATERBASED Limit: 140 g/I VOC (2007); 140 g/I VOC (2010) This product contains max: < 140 g/I VOC





Pallet of 120 boxes of 12 x 310 ml



**Preparation** Ready to use



Performance in a 5mm thick layer and 1cm in width

50 - 60 g/lineal metre



7.0 - 9.0



Maximum thickness per layer 10 mm



**Adherence** > 14 Kg/cm<sup>2</sup> on concrete



Fire classification D - s2 - d0



**Use time** No limits



**Drying in 1 mm thickness** 6-7H



**Maximum granulometry** 

10 microns without fibre



BAIXENS ESPAÑA / PORTUGAL POL. IND. MONCARRA, S/N 46230 ALGINET - VALENCIA (ESPAÑA) T.: 961.750.834 F.: 961.752.471

BAIXENS FRANCE 14, RUE DU PONT NEUF 75001 PARIS (FRANCE) T: 0.800.90.14.37 F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA VIA PIETRO NENNI, 36 46019 CICOGNARA - MANTOVA (ITALY) T.: 0375/88181/790016 F.: 0375/88831