

B-36

PLASTER SMOOTHING PASTE

Product designed to cover plasticised plaster and renew rough, pitted or embossed surfaces.



CLASSIFICATION ACCORDING TO STANDARD EN 16566

G3S2V3W2A0C0R0

SURFACES

Plaster, plaster of Paris, plasterboard, cement, concrete, non-elastic plastic paint. Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Easy to apply, smooth and sand.
- Fast setting.
- Fine and smooth finishes.
- Non-repellent.
- Good coverage.
- Storage: 12 months in its original packaging and protected from moisture.

IDEAL FOR

- Renovating and levelling painted surfaces.
- Smoothing of walls with defects (scratches, lines, knocks, etc.).



Pallet of 66 sacs
of 15 Kg



Pallet of 35 boxes
of 4 x 5 Kg

**Mixing water ratio**

0,40-0,45 litres of water per kg of plaster

**Performance**

0,60 m²/kg



6.5 - 7.5

**Maximum application thickness**

4 mm for plastering
Unlimited for filling

**Adherence**

> 8 Kg/cm² on cement and paint

**Fire classification**

A1

**Use time**

1 H 30' - 2 H

**Drying in 1 mm thickness**

Concrete and paint: 6 - 7 H
Plaster: 2 - 3 H

**Maximum granulometry**

300 microns



BAIXENS ESPAÑA
POL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE
14, RUE DU PONT NEUF
75001 PARIS (FRANCE)
T.: 0.800.90.14.37
F.: 0.800.90.20.52

BAIXENS ITALIA / BULOVA
VIA PIETRO NENNI, 36
46019 CICOGNARA - MANTOVA (ITALY)
T.: 0375/88181/790016 F.: 0375/88831
www.bulova-pennelli.com

BAIXENS PORTUGAL / ARGATINTAS
AVENIDA PORTAS DO MINHO, Nº 711
4760 - 706 RIBEIRÃO,
V.N. FAMALICÃO
T.: 252 910 030 | www.argatintas.pt

B36NF1526A20