

B-37





ANTI-MOISTURE BARRIER

Waterproofing powder for anti-moisture treatment.









COVERING

FOR ALL TYPES OF CONVENTIONAL PAINT
AFTER COMPLETE DRYING

SURFACES

Plaster, plaster of Paris, cement, stone, concrete, etc. Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

CHARACTERISTICS

- Normal setting.
- Easy to apply.
- · Protective barrier against moisture.
- · Water vapour permeable.
- Waterproof.
- Applicable by brush (as paint) or by trowel or spatula (as plaster).
- It acts under both positive and negative pressure.
- Storage: 12 months in its original packaging and protected from moisture.

IDEAL FOR

- Sealing, coating and protecting all surfaces exposed to aggressivity from water and moisture, both outside and inside, such as basements, underground foundations, swimming pools, planters, etc.
- Moisture control and increased resistivity for concrete structures in accordance with UNE-EN 1504-2.









Mixing water ratio

0.40 litres of water per kg of powder (paint consistency) 0.30 litres of water per kg of powder (plaster consistency)



Performance 1 - 1,5 kg/m²



12.0 - 13.0



Maximum thickness per layer 10 mm for plastering 3 mm as a paint application



Adherence > 7 Kg/cm² on cement



Fire classification A1



Use time



Drying in 1mm thickness

Concrete: 3 - 4 H



Maximum granulometry
900 microns



BAIXENS ESPAÑAPOL. IND. MONCARRA, S/N
46230 ALGINET (VALENCIA)
T.: 961.750.834
F.: 961.752.471

BAIXENS FRANCE 14, RUE DU PONT NEUF 75001 PARIS (FRANCE) T.: 0.800.90.14.37 F.: 0.800.90.20.52 BAIXENS ITALIA / BULOVA VIA PIETRO NENNI, 36 46019 CICOGNARA - MANTOVA (ITALY) T.: 0375/88181/790016 F.: 0375/88831 www.bulova-pennelli.com BAIXENS PORTUGAL / ARGATINTAS AVENIDA PORTAS DO MINHO, Nº 711 4760 - 706 RIBEIRÃO, V.N. FAMALICÃO T.: 252 910 030 | www.argatintas.pt

B37NF1893A20