

CX-61G

Colbaix®

## MORTERO TIXOTRÓPICO DE REPARACIÓN

Thixotropic repair mortar suitable for repairing and restoration of exterior façades



EXTERIOR



### USES

Cement, stone, brick, concrete, non-elastic synthetic paint and any type of absorbent substrate in construction.

Surfaces should be healthy, dry, cohesive, absorbent, clean and free from dust.

### FEATURES

- Easy to apply and great loading power in each coat.
- Easy to mix.
- Fast absorption which allows and immediate go over.
- Waterproofed and fibered product.
- Low retraction.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

### IDEAL FOR

- Repairing concrete in thick layers on walls and ceilings.
- Grouting joints of pre-fabricated elements.
- Repairing chips and impairments on buildings, bridges and infrastructures.
- Renovating and restoration of chips on cement and concrete substrates.
- Plastering and regularization of concrete, cement or mortar surfaces.

CODE (EN 16566)

G3S2V3W2A0C0R0



Pallet of 48  
sacks of 20 Kg



Pallet of 35 cases  
of 4 x 5 Kg



#### Water for mixing

0.26 – 0.27l of water per kg of powder



1.65 - 1.75 Kg/m<sup>2</sup>/mm



12.0 - 13.0



#### Maximum thickness per layer

Minimum: 5mm  
Maximum: 80mm



#### Adhesion

> 16Kg/cm on cement



#### Fire classification

A1



#### Service Life

1 hr 30' – 2 hrs.30'



#### Drying Time

Concrete: 4 – 5 hrs.



#### Maximum granulometry

1000 µm