

E-07

Enlucite[®]

RENOVATION FR

Suitable for fast and effective covering of laminated stipple paint and renovating uneven surfaces



INTERIOR



USES

Gypsum, plaster, gypsum plasterboards, cement, laminated stipple paint and non-elastic plastic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES & USES

- Fast setting.
- Easy to apply, smooth and sand.
- Possibility of going over before drying.
- Excellent covering power.
- Applicable in thick layer to cover imperfections.
- Smoothing stipple painted walls.
- Renovating painted walls.
- Levelling vertical substrates.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE COMPLETELY DRY

CODE (EN 16566):

G3S2V3W2A0C0R0


Pallet of 66 sacks
of 15 kg.



Pallet of 35 cases
of 4 x 5 kg.



Water for mixing

0,40 – 0,45 litres of water per kg of plaster



Performance in 1mm layer

1.45 - 1.55 Kg/m²



6.5 - 7.5



Maximum thickness per layer

10 mm



Adhesion

> 5 Kg/cm² on cement & paint.



Fire classification

A1



Useful life

1 H 45' - 2 H 15'



Drying in 1mm thickness

Concrete, plaster & paint: 2- 3 hrs.



Maximum granulometry

300 microns