

E-15

Enlucite®

FINISHING PROJECTION PLASTER

Projection plaster in powder suitable for smoothing absorbent surfaces.



INTERIOR



USES

Gypsum, plaster, smooth cement, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES & USES

- Non-setting.
- Excellent workability.
- Easy to level and smooth.
- Easy to sand.
- Smooth and fine finishes.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE COMPLETELY DRY

CODE (EN 16566):

G3S2V2W2A0C0R0



Pallet of 66 sacks
of 15 kg.



Pallet of 35 cases
of 4 x 5 kg.



Water for mixing

0,40 – 0,45 litres of water per
kilo of plaster



Performance in 1mm layer

1.55 – 1.67 Kg/m²



8.5 - 9.5



Maximum thickness per layer

1 mm



Adhesion

> 10 Kg/cm² on cement & Paint



Fire classification

A2 - s1 - d0



Useful life

Non-setting



Drying in 1mm thickness

Plaster, paint & concrete: 8 hrs.



Maximum granulometry

200 microns