

E-16

Enlucite®

## RENOVATING PROJECTION PLASTER

Projection plaster in powder suitable for renovating and covering irregular and stipple paint bases



### USES

Gypsum, plaster, cement, concrete, fibre-glass, laminated stipple, brick, pre-fab blocks, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES & USES

- Non-setting.
- Excellent workability, easy to level and smooth.
- Easy to sand.
- Smoothing and renovating embossed walls and ceilings.
- Smooth and fine finishes.
- Levelling of substrates.
- Renovation of damaged substrates.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



### RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS  
ONCE COMPLETELY DRY

CODE (EN 16566):

**G3S2V2W2A0C0R0**



Pallet of 66 sacks  
of 15 kg.



Pallet of 35 cases  
of 4 x 5 kg.



#### Water for mixing

0,40 – 0,45 litres of water per kilo of plaster



#### Performance in 1mm layer

1.40 – 1.70 Kg/m<sup>2</sup>



7.5 - 8.5



#### Maximum thickness per layer

3 - 4 mm



MPa

#### Adhesion

> 8 Kg/cm<sup>2</sup> on cement & paint.



#### Fire classification

A2 - s1 - d0



#### Useful life

Non-setting



#### Drying in 1mm thickness

Plaster & paint: 6 hrs  
Concrete: 24 hrs.



#### Maximum granulometry

300 microns