

E-21

Enlucite®

## SPECIAL WAX

Obtaining of rustic walls endowed with acoustic muffling and thermal insulation.

INTERIOR



### INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I, HIGH PERFORMANCE ONE COMPONENT  
WATER-BASED COATINGS

LIMIT: 140G/L COV (2007); 140g/l COV(2010)

This product contains 0,12g/l COV max.

### RECOAT

BY FINISHING WAX RX-502 CERALAIX

CODE (EN 16566):

**G3S3V2W2A0C0R0**

## USES

Gypsum, plaster, cement, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

## FEATURES & USES

- Does not require sanding.
- Easy to apply in one step.
- Soft touch finishes.
- Absence of splices.
- Possibility of covering gaps or small holes.
- Possibility of re-touching the shapes created before starting to set.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



25Kg

Pallet of 33  
buckets of 25 kg.



### Preparation

Ready to use.  
Clean tools with water.



### Performance

1.50 - 1.60 Kg/m<sup>2</sup>/mm



7.0 - 8.0



### Maximum thickness per layer

2 mm



### Adhesion

> 13 Kg/cm<sup>2</sup> on cement & Paint.



### Fire classification

A2 - s1 - d0



### Useful life

Unlimited



### Drying in 1mm thickness

Cemento y pintura: 12 H aprox.



### Granulometry

400 microns