

E-24

Enlucite®

FILLERS FR

Plaster for the interior for filling in and covering cavities and non-structural cracks. Quick dry



INTERIOR



USES

Gypsum, plaster, cement, pre-fabs and non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES & USES

- Quick setting.
- Quick dry.
- No shrinkage or cracking.
- Contains anti-cracking agents.
- Applicable in thin or thick layer.
- Easy to sand.
- Easy to apply.
- For covering union joints.
- For pasting moulds.
- For covering non-structural cracks.
- Storage: 6 months inside its original packing and kept free from damp and humidity.



RECOAT

BY ALL TYPES OF NON-ELASTIC PAINTS
ONCE COMPLETELY DRY

CODE (EN 16566):

G3S2V3W2A0C0R0


Pallet of 66 sacks
of 15 kg.



Pallet of 33 cases
of 4 x 5 kg.



Pallet of 36 cases
of 20 x 1 kg.



Water for mixing

0,47 – 0,53 litres of water per
Kg of plaster



Performance in 1mm layer

1.50 - 2.00 Kg/m²



6.5 - 7.5



Maximum thickness per layer

10 mm. for plastering
Unlimited for covering



Adhesion

> 10 Kg/cm² on cement
> 9 Kg/cm² on paint



Fire classification

A2 - s1 - d0



Useful life

35 - 60 min



Drying in 1mm thickness

Plaster: 3 – 4 hrs.
Concrete & Paint: 6 – 7 hrs.



Maximum Granulometry

300 microns