

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 1 of 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: **CONCRETE ACRYLPRIMER**
Product Code: **CX-37**
Internal Code: **CX37NF3286A26**

1.2 Relevant identified uses of the substance or mixture and uses advised against.

High-adhesion multi-surface primer, designed as a base coat for painting on low or non-absorbent substrates.

We recommend carefully reading the corresponding Technical Data Sheet.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **ESTABLECIMIENTOS BAIXENS S.L.**
Address: Pol. Industrial Moncarra, s/nº
City: 46230 - ALGINET
Province: VALENCIA
Telephone: 96 175 08 34
Fax: 96 175 93 92
E-mail: laboratorio@baixens.com
Web: www.baixens.com

1.4 Emergency telephone number: 961 750 834 (Only available during office hours; Monday-Friday; 08:00-18:00)

Toxicological Information Service (National Institute of Toxicology and Forensic Science) Telephone: +34 91 5620420.

Information in Spanish (24h/365 days). Intended with the only purpose of providing medical assistance in an emergency situation.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P273 Avoid release to the environment.

P501 Dispose of the content and/or its container as a hazardous waste, through an authorized waste management company, in accordance with the current regulations.

EUH statements:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-1,2-thiazol-3(2H)-one-5-chloro-2-methyl-1,2-thiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains: • Diuron • Zinc salts of pyridine-1-oxy-2-thiol • 2-octyl-2H-isothiazol-3-one • Zinc oxide.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 2 of 11

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture contains endocrine disrupting properties substances in a concentration lower than 0.1%

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
N. CAS: 13463-67-7 N. CE: 236-675-5 N. registro: 01-2119489379-17-XXXX	Titanium dioxide	5 - 10 %	-	-
Index No: 613-333-00-7 CAS No: 13463-41-7 EC No: 236-671-3 Registration No: 01-2119511196-46-XXXX	pyrithione zinc, (T-4)- bis[1-(hydroxy-.kappa.O)pyridine-2(1H)- thionato-.kappa.S]zinc	0 - 0.025 %	Acute Tox. 2, H330 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=1000) - Aquatic Chronic 1, H410 (M=10) - Eye Dam. 1, H318 - Repr. 1B, H360D - STOT RE 1, H372	Inhalation: ETA = 0.14 mg/l (Armonizada ATP 15) Oral: ETA = 221 mg/kg pc (Armonizada ATP15)
Index No: 613-088-00-6 CAS No: 2634-33-5 EC No: 220-120-9 Registration No: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	0.01 - 0.036 %	Acute Tox. 2, H330 - Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1) - Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1A, H317	Skin Sens. 1A, H317: C ≥ 0,036 % Inhalation: ETA = 0.21 mg/L (ATP 21) Oral: ETA = 450 mg/kg bw (ATP 21)
Index No: 006-015-00-9 CAS No: 330-54-1 EC No: 206-354-4 Registration No: 01-2119517622-45-XXXX	diuron (ISO), 3-(3,4-dichlorophenyl)-1,1-dimethylurea	0.0025 - 0.025 %	Aquatic Acute 1, H400 (M=100) - Aquatic Chronic 1, H410 (M=100) - Carc. 1B, H350 - STOT RE 2, H373	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 3 of 11

Index No: 613-112-00-5 CAS No: 26530-20-1 EC No: 247-761-7 Registration No: 01-2120768921-45-XXXX	octhiline (ISO), 2-octyl-2H-isothiazol-3-one	0.0015 - 0.0025 %	Acute Tox. 2, H330 - Acute Tox. 3, H311 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=100) - Aquatic Chronic 1, H410 (M=100) - Eye Dam. 1, H318 - Skin Corr. 1, H314 - Skin Sens. 1A, H317, EUH071	Skin Sens. 1A, H317: C ≥ 0,0015 % Dermal: ETA = 311 mg/kg bw (ATP 15) Inhalation: ETA = 0.27 mg/L (ATP 15) Oral: ETA = 125 mg/kg bw (ATP 15)
Index No: 613-167-00-5 CAS No: 55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	0 - 0.0015 %	Acute Tox. 2, H310 - Acute Tox. 2, H330 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=100) - Aquatic Chronic 1, H410 (M=100) - Eye Dam. 1, H318 - Skin Corr. 1C, H314 - Skin Sens. 1A, H317, EUH071	Skin Corr. 1C, H314: C ≥ 0,6 % Skin Irrit. 2, H315: 0,06 % ≤ C < 0,6 % Eye Irrit. 2, H319: 0,06 % ≤ C < 0,6 % Skin Sens. 1A, H317: C ≥ 0,0015 % Eye Dam. 1, H318: C ≥ 0,6 %
Index No: 613-326-00-9 CAS No: 2682-20-4 EC No: 220-239-6 Registration No: 01-2120764690-50-XXXX	2-methylisothiazol-3(2H)-one	0 - 0.0015 %	Acute Tox. 2, H330 - Acute Tox. 3, H311 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 (M=1) - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317, EUH071	Skin Sens. 1A, H317: C ≥ 0,0015 %

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 4 of 11

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. If the person vomits, clear the respiratory tract. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022
Version 2 (replaces version 1) Revision date: 22/06/2026

Page 5 of 11

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Application of the product in the conditions and supports indicated in the FT of the same. Uses specified in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
diuron (ISO), 3-(3,4-dichlorophenyl)-1,1-dimethylurea CAS No: 330-54-1 EC No: 206-354-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	0,17 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Primer
Breathing protection:	
If the recommended technical measures are observed, no individual protection equipment is necessary.	
Hand protection:	
If the product is handled correctly, no individual protection equipment is necessary.	
Eye protection:	
If the product is handled correctly, no individual protection equipment is necessary.	
Skin protection:	
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 6 of 11

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Corresponding to the one selected from your sample card.

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: > 60 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: 8.0 – 10.0

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product

Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 1.16±0.07 gr/cm³

Relative vapour density: Not applicable/Not available due to the nature/properties of the product

Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: 6000-11000 cP (A/4/10)

Explosive properties: Not applicable/Not available due to the nature/properties of the product

Oxidizing properties: Not applicable/Not available due to the nature/properties of the product

Dropping point: Not applicable/Not available due to the nature/properties of the product

Solids content: 29-34%

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Toxicological information about the substances present in the composition.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 7 of 11

Name	Acute toxicity			
	Type	Test	Kind	Value
1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one CAS No: 2634-33-5 EC No: 220-120-9	Oral	LD50	Rat	1020 mg/kg bw [1] [1] Pharmacological Research Communications. Vol. 3, Pg. 385, 1971
	Dermal			
	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

"Not skin sensitiser based on the results of similar mixtures tested in accordance with the extrapolation principles described in Article 9(4) of the CLP Regulation; OECD 429 LLNA (mouse) - not skin sensitiser – S4565 "

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Based on available data, the classification criteria are not met.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
	Fish	LC50	Fish	10 mg/l (96 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 8 of 11

1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one		[1] Linden, E., B.E. Bengtsson, O. Svanberg, and G. Sundstrom 1979. The Acute Toxicity of 78 Chemicals and Pesticide Formulations Against Two Brackish Water Organisms, the Bleak (<i>Alburnus alburnus</i>) and the Harpacticoid <i>Nitocra spinipes</i> . Chemosphere 8(11/12):843-851 (Author Communication Used) (OECDG Data File)
	Aquatic invertebrates	EC50 Crustacean 4,4 mg/l (48 h) [1] [1] Office of Pesticide Programs 2000. Pesticide Ecotoxicity Database (Formerly: Environmental Effects Database (EEDB)). Environmental Fate and Effects Division, U.S.EPA, Washington, D.C
	Aquatic plants	
CAS No: 2634-33-5 EC No: 220-120-9		

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

Substances with endocrine disrupting properties can cause in living organisms: hormone imbalance, decrease in the quality and quantity of gametes, fertility problems, alteration of reproductive behaviors, deformation of sexual organs, embryonic abnormalities, changes in the sex ratio of a species and / or developmental delays.

12.7 Other adverse effects.

The product is not affected by the Regulation (EU) 2024/590 of the European Parliament and of the Council of 7 February 2024 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 9 of 11

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Not classified as hazardous for transport.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product subcategory: **Primers, water-based.**

Phase I* (from 1.1.2007): **50**

Phase II* (from 1.1.2010): **30**

* g/l ready to use

VOC content (g/l): **<30 g/l**

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

Substances including by Regulation (EU) No 649/2012 concerning the export and import of dangerous chemicals:

Name	
diuron (ISO); 3-(3,4-dichlorophenyl)-1,1-dimethylurea	
CAS No: 330-54-1	
EC No: 206-354-4	
Annex I Part 1 - Subcategory	Limitation
Pesticide in the group of plant protection products	Ban
Annex I Part 2 - Category	Limitation
Pesticides	Severe restriction

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 Date of compilation: 15/11/2022

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 10 of 11

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H350	May cause cancer.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Complete text of the EUH phrases that appear in section 3:

EUH071 Corrosive to the respiratory tract.

Classification codes:

Acute Tox. 2: Acute toxicity (Dermal), Category 2
Acute Tox. 2: Acute toxicity (Inhalation), Category 2
Acute Tox. 3: Acute toxicity (Dermal), Category 3
Acute Tox. 3: Acute toxicity (Oral), Category 3
Acute Tox. 4: Acute toxicity (Oral), Category 4
Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 3: Chronic effect to the aquatic environment, Category 3
Carc. 1B: Carcinogen, Category 1B
Eye Dam. 1: Serious eye damage, Category 1
Repr. 1B: Reproductive toxicant, Category 1B
STOT RE 1: Specific target organ toxicity following a repeated exposure, Category 1
STOT RE 2: Specific target organ toxicity following a repeated exposure, Category 2
Skin Corr. 1: Skin Corrosive, Category 1
Skin Corr. 1B: Skin Corrosive, Category 1B
Skin Corr. 1C: Skin Corrosive, Category 1C
Skin Irrit. 2: Skin irritant, Category 2
Skin Sens. 1: Skin sensitiser, Category 1
Skin Sens. 1A: Skin sensitiser, Category 1A

Changes regarding to the previous version:

- Changes in the identification of the substance or mixture (SECTION 1)
- Changes in label elements (SECTION 2.2)
- Changes in composition/information on ingredients (SECTION 3.2)
- Changes in exposure controls (SECTION 8.1)
- Changes in physical and chemical properties (SECTION 9)
- Changes in toxicological information (SECTION 11)
- Changes in regulatory information (SECTION 15)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

CONCRETE ACRYLPRIMER



Version 1 **Date of compilation: 15/11/2022**

Version 2 (replaces version 1)

Revision date: 22/06/2026

Page 11 of 11

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.