(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Version: 1 Page 1 of 9

Revision date: 13/05/2020

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: ACRILASTIC PRO

Product Code: PX-33

1.2 Relevant identified uses of the mixture and uses advised against.

Super elastic waterproofing material for terraces professional.

We recommend to read its Technical Data Sheet carefully.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: ESTABLECIMIENTOS BAIXENS S.L.

Address: Pol. Industrial Moncarra, s/nº

City: 46230 ALGINET
Province: VALENCIA
Telephone: 96 175 08 34
Fax: 96 175 93 92

E-mail: <u>laboratorio@baixens.com</u>

1.4 Emergency telephone number: 961 750 834 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

The product is not classified as hazardous within the meaning of Regulation (EU) No 1272/2008.

2.2 Label elements.

EUH statements:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-1,2-thiazol-3(2H)-one-5-chloro-2-methyl-1,2-thiazol-3(2H)-

one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

This mixture does not contain substances that pose a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, are not assigned a Community exposure limit in the workplace, and are not classified as PBT/vPvB or included in the Candidate List:

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO

Version: 1 Revision date: 13/05/2020 Page 2 of 9

	Nom	Concentration	(*)Classification Règlement (CE) No 1272/2008	
Identifiants			Classification	Limites de concentration spécifiques
N. CAS: 2634-33-5 N. CE: 220-120-9	1,2-benzisothiazol-3(2H)-one	0.0165 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 - Eye Dam. 1, H318 - Skin Irrit 2. H315 - Skin Sens. 1, H317	Skin Sens. 1, H317: C ≥ 0,05 %
N. CAS: 55965-84-9 N. CE: -	2-methyl-1,2-thiazol-3(2H)-one-5-chloro-2-methyl-1,2-thiazol-3(2H)-one	0.00135 %	Acute Tox. 3, H301 - Acute Tox. 2, H310 - Acute Tox. 2, H330 - Aquatic Acute 1, H400 - - Skin Corr. 1C, H314 - Skin Sens. 1A, H317	Skin Sens. 1A, H317: C ≥ 0,0015 %
N. CAS: 13463-41-7 N. CE: 236-671-3	Pyrithione zinc	0.0229 %	Acute Tox. 3, H301 - Aquatic Acute 1, H400 - Eye Dam. 1, H318 - Aquatic Chronic 1, H410 - Acute Tox. 4, H332	-
N. CAS: 1314-13-2 N. CE: 215-222-5	Zinc oxide	0.085 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-
N. CAS: 330-54-1 N. CE: 206-354-4	3-(3,4-dichlorophenyl)-1,1-dimethylurea	0.008 %	Acute Tox. 4, H302 – Carc. 2, H351 – STOT RE 2, H373 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-
N. CAS: 26530-20-1 N. CE: 247-761-7	2-octyl-2H-isothiazol-3-one f the H phrases is given in section 16 of this Safety is	0.0032 %	Acute Tox. 4, H302 - Acute Tox. 3, H311 - Skin Corr. 1B, H314 - Skin Sens. 1, H317 - Acute Tox. 3, H331 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	Skin Sens. 1, H317: C ≥ 0,05 %

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet. [1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Page 3 of 9

Version: 1

Revision date: 13/05/2020

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Due to the composition and type of the substances present in the product, no particular warnings are necessary.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eve contact

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing.

Ingestion.

Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Page 4 of 9

Version: 1

Revision date: 13/05/2020

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The product does not require special handling measures, the following general measures are recommended:

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

The product does not require special storage measures.

As general storage measures, sources of heat, radiation, electricity and contact with food should be avoided.

Keep away from oxidising agents and from highly acidic or alkaline materials.

Store the containers between 5 and 35° C, in a dry and well-ventilated place.

Store according to local legislation. Observe indications on the label.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Professional application of the product on the supports indicated in the Technical Data Sheet.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %				
Uses:					
Breathing protect	Breathing protection:				
If the recommende	d technical measures are observed, no individual protection equipment is necessary.				
Hand protection:					
PPE: Characteristics:	Protective gloves. «CE» marking, category II.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420 Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible.				
Maintenance:	ot make any changes to the gloves that may alter their resistance, or apply paints, solvents or sisters.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Version: 1 Page 5 of 9 Revision date: 13/05/2020

Breakthrough time Material thickness 0,35 Material: > 480 PVC (polyvinyl chloride) (min.): (mm): Eye protection: PPE: Face shield. Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 CFN standards: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance: be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm Observations: vertically once attached to the frame. Skin protection: PPE: Protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics: order not to obstruct the user's movements. CEN standards: EN 340 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance: the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in Observations: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPE: Work footwear. Characteristics: «CE» marking, category II. CEN standards: EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should Maintenance: not be used by other people. Work footwear for professional use includes protection elements aimed at protecting users against any Observations: injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid of average viscosity Colour: Corresponding to the elect of their letter

Odour: Characteristic Odour threshold: N.A./N.A.

pH: 7.0-8.0

Melting point: N.A./N.A. Boiling Point: N.A./N.A. Flash point: N.A./N.A. Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density: N.A./N.A.

Relative density: 1.25±0.07 gr/cm3

Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: (A/6/10): 35000-55000 cP Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO

Version: 1 Page 6 of 9
Revision date: 13/05/2020



9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Version: 1 Page 7 of 9
Revision date: 13/05/2020

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous.

ICAO/IATA: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Version: 1 Page 8 of 9
Revision date: 13/05/2020

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product subcategory: one-pack performance coating, water-borne

Phase I* (from 1.1.2007): **140** Phase II* (from 1.1.2010): **140**

* g/l ready to use

VOC content (g/l): 28 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

Toxic if swallowed

H302	Harmful if swallowed
H310	Fatal in contact with skin
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H351	Suspected of causing cáncer
H373	May cause damage to organs through prolonged or repeated exposure

Classification codes:

H301

Acute Tox. 4 : Acute toxicity (Oral), Category 4 Acute Tox. 3 : Acute toxicity (Oral), Category 3 Acute Tox. 2 : Acute toxicity (Oral), Category 2

Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1

Eye Dam. 1 : Serious eye damage, Category 1 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Irrit. 2 : Skin irritant, Category 2 Skin Corr. 1 : Skin Corrosive, Category 1

Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1

(in accordance with Regulation (EU) 2015/830)

ACRILASTIC PRO



Carc. 2: Carcinogen, Category 2

STOT SE 2: Toxicity in certain organs after repeated exposures, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is recommended that the product only be employed for the purposes advised.

Abbreviations and acronyms used:

CEN: European Committee for Standardization.

PPE: Personal protection equipment.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

