

PX-01

Imper

WASH-IMPER

High quality waterproof elastic acrylic for use in proofing and restoring horizontal settings such as terraces, decks or covers/roofs.



BEFORE THE APPLICATION OF THIS PRODUCT
CONSULT OUR APPLICATION MANUAL AND / OR
DEMONSTRATIVE VIDEO

INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I1, HIGH PERFORMANCE ONE COMPONENT
COATINGS WATER-BASED

LIMIT: 140G/L COV (2007); 140g/l COV(2010)
This product contains 22,62 g/l COV max.



USE

Cement, cast concrete, hollow bricks, Catalan tiles, other absorbent prefabricated materials used in construction.

Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of having fiberglass included in this product.
- Washable elastic protective covering.
- Water vapour resistant
- Resistant to moderate transit or technical access.
- Excellent adhesion
- Resistant to the alkalinity of the surface.
- Available in 8 colours
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Waterproofing and restoration of terraces, covers and outdoor settings
- Suitable for waterproofing of vertical settings.
- Protection of cellular concrete, polyurethane foam and fibre cement panels



25Kg Pallet of 33
pots of 25 kg

15l Pallet of 33
pots of 15l

4l Pallet of 120 pots
of 4 l.

750ml Pallet de 44 boxes
of 12 x 750 ml.



PREPARATION

Ready to use.



PERFORMANCE

1.73-2.61/m² in 2 coats of material



7.0 - 8.0



Apply with brush, roller,
Cleaning of tools



CLEANING OF TOOLS

Use water agua



FIRE CLASSIFICATION

D - s2 - d0



USEFUL LIFE

Unlimited