

PX-02

Imper

ELASTINE

Acrylic water-proofer for use in proofing and restoring terraces, decks or covers/roofs exposed to the outside.



BEFORE APPLYING THIS PRODUCT
CHECK OUT THE APPLICATIONS
MANUAL AND/OR DEMO VIDEO

INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY I, ONE COMPONENT WATER-BASED
HIGH PERFORMANCE COATINGS

Limit: 140g/l COV (2007); 140 g/l COV (2010)
This product contains: 23,78 g/l COV max.

SUBSTRATES AND USES

Cement, concrete, hollow bricks, Catalan tiles, other absorbent prefabricated materials used in construction.

Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of having fiberglass included in this product.
- Washable elastic protective covering.
- Permeable to water vapour.
- Resistant to moderate transit or technical access.
- Excellent adhesion
- Resistant to the alkalinity of the substrate.
- Available in 8 colours.
- Coating for humidity control.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Waterproofing and restoration of terraces, covers and outdoor settings
- Suitable for waterproofing of vertical settings.
- Protection of aerated concrete, polyurethane foam and fibre cement sheets.



15l Pallet of 33
buckets of 15 l.

4l Pallet of 120
buckets of 4 l.

750ml Pallets of 44 cases
of 12 x 750 ml.



Preparation
Ready to use



Rendimiento
1.5-2.0 l/m² in 2 coats of material



7.5 - 8.5



Apply with brush, roller, airless sprayer



Cleaning of tools
Use water



Fire classification
E - d0



Useful life
Unlimited



Density
1,15 ± 0,07



Viscosity
35000 - 55000