

PX-03

Imper

ACRILASTIC

Waterproofing anti-leaks, ideal for waterproofing and restoration of terraces, covers or roofs and traditional settings exposed to the outdoors



BEFORE THE APPLICATION OF THIS PRODUCT
CONSULT OUR APPLICATION MANUAL AND / OR
DEMONSTRATIVE VIDEO

INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY I, HIGH PERFORMANCE ONE COMPONENT
COATINGS WATER-BASED

LIMIT: 140g/L COV (2007); 140g/l COV(2010)
This product contains 32,38 g/l COV max.



USE

Cement, cast concrete, hollow bricks, Catalan tiles, other absorbent prefabricated elements used in construction.

Surfaces should be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of having fiberglass included in this product.
- Washable elastic protective covering.
- Water vapour resistant
- Resistant to moderate transit or technical access.
- Excellent adhesion
- Resistant to the alkalinity of the surface.
- Available in 9 colours
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Waterproofing and restoration of terraces, covers or roofs and outdoor settings
- Suitable for waterproofing of vertical settings.
- Protection of cellular concrete, polyurethane foam and fibre cement panels



15l Pallet de 33 pots
of 15l.

4l Pallet de 120 pots
de 4l.

750ml Pallet de 44 boxes
of 12 x 750 ml.



PREPARATION

Ready to use.



PERFORMANCE

1.6-2.0l/m² in 2 coats of material



7.0 - 8.0



Apply with brush, roller,
Cleaning of tools



CLEANING OF TOOLS

Use water agua



FIRE CLASSIFICATION

D - s2 - d0



USEFUL LIFE

Sin límite