

PX-04

Imper

WASH-IMPER

High quality elastic-acrylic water-proofer for use in vertical facings such as façades and inner courtyards.



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I1, ONE COMPONENT WATER-BASED
HIGH PERFORMANCE COATINGS

Limit: 140g/l COV (2007); 140 g/l COV (2010)
This product contains: 23,10 g/l COV max.



SUBSTRATES AND USES

Cement, concrete, brick, pre-fabs and other absorbent materials used in construction. Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Washable elastic protective covering.
- Permeable to water vapour.
- Excellent adhesion.
- Protects substrates from carbonation.
- Resistant to the alkalinity of the substrate.
- Available in 10 colours.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Waterproofing vertical facings (façades, inner courtyards, etc.).
- Protection of polyurethane foam.



15l Pallet of 33 buckets of 15 l. 4l Pallet of 120 buckets of 4 l.



Preparation

Ready to use



Performance

0.77 - 1.15 l/m² in 2 coats of material



7.5 - 8.5



Apply with brush, roller, airless sprayer



Cleaning of tools

Use water



Fire classification

E - d0



Useful life

Unlimited