

PX-05

Imper

ELASTINE

Elastic-acrylic water-proofer and decorator for use in vertical facings exposed to the exterior.



INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY I, ONE COMPONENT WATER-BASED
HIGH PERFORMANCE COATINGS

Limit: 140g/l COV (2007); 140 g/l COV (2010)
This product contains: 23,21 g/l COV max.

EXTERIOR



SUBSTRATES AND USES

Cement, concrete, brick, pre-fabs and other absorbent materials used in construction. Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Washable elastic protective covering.
- Permeable to water vapour.
- Excellent adhesion.
- Protects substrates from carbonation.
- Resistant to the alkalinity of the substrate.
- Available in 10 colours.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Waterproofing vertical facings (façades, inner courtyards, etc.).
- Protection of polyurethane foam.



Pallet of 33
buckets of 15 l.



Pallet of 120
buckets of 4 l.



Preparation
Ready to use.



Performance
0.90 - 1.36 l/m² in 2 coats of material



7.5 - 8.5



Apply with brush, roller, airless sprayer



Cleaning of tools
Use water



Fire classification
D - s2 - d0



Useful life
Sin límite