

PX-07

Imper

REPELEX

Transparent non-film water resistant destined for the protection of facades and vertical surfaces exposed to the outdoors.



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY H2, CONSOLIDANT PRIMERS, SOLVENT-BORNE

LIMIT: 750 g/l COV (2007); 750 g/l COV(2010)

This product contains 739,53 g/l COV max.



USE

Cement, stone, brick, concrete, masonry and clinker brick. Surfaces should be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Transparent damp proofer.
- Penetrates, seals and protects surfaces without forming a film layer.
- Breathable product
- Self-cleaning
- Easy to apply
- Respects colour and the natural appearance of the surface.
- Great penetration power
- Prevents carbonisation
- Enhances the resistance against freezing temperatures
- Storage: 12 months year inside its original container and kept free from damp and humidity.

IDEAL FOR

- Protects surfaces from the aggressiveness or action of rain water.
- Protects from saltpetre and the forming of efflorescence
- Protects from erosion and dirt.

Pallet de 30 boxes
of 2 x 4 l.Pallet de 44 boxes of
8 x 750ml.**Preparation**
Ready to use.**Performance**
0.150 - 0.200 l/m²

5.0 - 6.0

Apply with brush, roller,
Cleaning of tools, Airless sprayer**Cleaning of tools**
Use solvent immediately after use**Fire classification**
B-s1-d0**Useful life**
Unlimited

Solvent-based product