

PX-130

Imper

ACRILDUR

Anti-leaks with high adherent power formulated based on acrylic resins for waterproofing horizontal settings (terraces).



BEFORE APPLYING THIS PRODUCT
CHECK OUT THE APPLICATIONS
MANUAL AND/OR DEMO VIDEO

INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY i1, ONE COMPONENT WATER-BASED
HIGH PERFORMANCE COATINGS

Limit: 140g/l COV (2007); 140 g/l COV (2010)
This product contains: 14 g/l COV max.



USE

Cement, concrete, hollow bricks, Catalan tiles, pre-fabs and other absorbent materials used in construction.

Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of having fiberglass included in this product.
- Washable elastic protective covering.
- Permeable to water vapour.
- Resistant to moderate transit or technical access.
- Excellent adhesion
- Resistant to the alkalinity of the substrate.
- Available in 9 colours.
- Coating for humidity control.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Waterproofing and restoration of terraces, covers and outdoor settings
- Suitable for waterproofing vertical settings.
- Protection of aerated concrete, polyurethane foam and fibre cement sheets.



Pallet of 33 buckets
of 15 l.



Pallet of 120
buckets of 4 l.



Preparation
Ready to use.



Performance
1.5-2.0 l/m² in 2 coats of material



7.0 - 9.0



Apply with brush, roller, airless sprayer



Cleaning of tools
Use water



Fire classification
D - s2 - d0



Useful life
Unlimited



Density
1,49 ± 0,07



Viscosity
40000 - 70000