

PX-15

Imper

ACRILASTIC

Water-proofer acrylic coating for protection of façades.
Textured finish.



INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY h1, WATER-BASED SINGLE COMPONENT
HIGH PERFORMANCE COATINGS

Limit: 140g/l COV (2007); 140 g/l COV (2010)
This product contains: 32,02 g/l COV max.



SUBSTRATES AND USES

Cement, concrete, brick and prefabricated materials and other absorbent elements used in construction.

Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Rough and matt finish.
- Elastic-protective washable coating.
- Permeable to water vapour.
- Absorbs fissures.
- Protects substrates from carbonation.
- Excellent adhesion.
- Permeable to rain water.
- Substrate alkalinity resistant.
- Available in 10 colours.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Water-proofing vertical facings (façades, interior courtyards, etc).
- Protecting from polyurethane foam.
- Control of humidity in concrete structures according to UNE-En 1504-2



15l Pallet of 33 buckets of 15 l. 4l Pallet of 120 buckets of 4 l.



Preparation
Ready to use.



Performance
0.8 – 1.2 ml/m² in 2 coats of material



8.0 - 10.0



Apply with brush, roller



Cleaning of tools
Use water



Viscosity
20000-30000



Useful life
Unlimited



Density
1,61 ± 0,07