

PX-18

Imper

## REPELEX SOLVENT-BASED ANTI-GRAFFITI

Colourless solvent-based anti-graffiti suitable for protecting surfaces from paints and/or graffiti.



### INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY h2, SOLVENT-BASED CONSOLIDATING PRIMERS

Limit: 750g/l COV (2007); 750 g/l COV (2010)  
This product contains: < 750 g/l COV max.

### SUBSTRATES AND USES

Cement, stone, brick, plaster, gypsum, prefabricated materials and other traditional absorbent or semi-absorbent substrates in masonry.

Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES

- Liquid product.
- Easy to apply.
- Prevents from carbonation.
- Preserves colour and tone of the surface treated.
- Excellent hydro-repelling power.
- High oil-repelling power.
- Breathable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

### IDEAL FOR

- Protecting vertical surfaces from paint and graffiti.
- Prevent from grease stains, felt-pens, oil or graffiti penetrating the substrate, facilitating its cleaning.



Pallet of 30 cases of  
2 x 4l.



Pallet of 44 cases  
of 8 x 750 ml.



**Preparation**  
Ready to use



**Performance**  
250 - 350 ml/m<sup>2</sup>



6.0 - 7.0



Apply with brush, roller, sprayer or  
airless blaster



**Cleaning of tools**  
Use white spirit



**Fire classification**  
D - s2 - d0



**Useful life**  
Unlimited



Solvent-based product