

PX-21

Imper

IRON WASH®

High adhesion elastic water proofing for multi surfaces



OUTDOOR



USE

Cement, concrete, aerated concrete, fibre cement, acrylic linings and old water proofing, hollow brick, Catalan tiles, metals (without previous priming) tiles, asphalt cloth and bituminous products, non-paraffined plastics PVC, PET, Polycarbonate...) polyurethane foam, asbestos-cement.

Surfaces should be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of product containing fibre glass.
- Large filling capacity
- Permeable to water vapour. Completely washable.
- Maintains its flexibility at low temperatures (3°C) and is resistant to high temperatures (80°C)
- Product reserved to technical access.
- High protection product.
- Available in 10 colours
- Storage: 12 months year inside its original container and kept free from damp and humidity.

IDEAL FOR

- Waterproofing facades and dividing walls, sloping roofs (slope of >/- 5%) and for leakage repairs, gutters and pipelines, glass roofs and repairs of holes.
- Encapsulation of asbestos according to decree D.M. 20th.August 1999 from the Republic of Italy.

BEFORE THE APPLICATION OF THIS PRODUCT
CONSULT OUR APPLICATION MANUAL AND / OR
DEMONSTRATIVE VIDEO

INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I, HIGH PERFORMANCE ONE COMPONENT
COATINGS WATER-BASED

LIMIT: 140G/L COV (2007); 140g/l COV(2010)
This product contains 32,24 g/l COV max.



15l Pallet of 33
pots of 15l

4l Pallet of 33
pots of 4l

750ml Pallet de 44 boxes
of 12 x 750 ml.



PREPARATION

Ready to use



PERFORMANCE

1.5 - 2.0 l/m² after 2 coats of material



7.0 - 8.0



Apply with brush, roller or airless.



CLEANING OF TOOLS

Use water only



FIRE CLASSIFICATION

E - d0



USEFUL LIFE

Unlimited