

PX-24

Imper

AQUAGUM

Anti-leakage destined to water-proofing and restoring terraces, decks and traditional substrates exposed to the exterior.



BEFORE APPLYING THIS PRODUCT
CHECK OUT THE APPLICATIONS
MANUAL AND/OR DEMO VIDEO

INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY I1, ONE COMPONENT WATER-BASED
HIGH PERFORMANCE COATINGS

Limit: 140g/l COV (2007); 140 g/l COV (2010)
This product contains: 32,28 g/l COV max.



SUBSTRATES AND USES

Cement, concrete, hollow bricks, Catalan tiles, ptr-fabs and absorbent elements used in construction.

Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Possibility of product containing fibre-glass.
- Washable elastic-protective coating.
- Permeable to water vapour.
- Product resistant to moderate transit o technical access.
- Excellent adhesion.
- Resistant to substrate alkalinity.
- Available in 9 colours.
- Coating for humidity control.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Water-proofing and restoring terraces , decks and exterior substrates.
- Suitable for water-proofing vertical substrates.
- Protecting aerated concrete, polyurethane foam and fibre-cement sheets.



12l

Pallet of 44
buckets of 12 l.

4l

Pallet of 120
buckets of 4 l.



Preparation
Ready to use.



Performance
1.5 – 2.0 l/m² in 2 coats of material



7.0 – 8.0



Apply with brush, roller, sprayer or airless blaster.



Cleaning of tools
Use white spirit



Fire classification
D – s2 – d0



Useful life
Unlimited



Density
1,40 ± 0,07



Viscosity
45000-75000