(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR



Revision date: 05/06/2025



Page 1 of 10

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: ACRILASTIC PUR

Product Code: PX-34

Internal Code: PX34NF3199A25

UFI: HNU8-10AP-Q009-XF0W

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Water-proofer based on binding acrylics and polyurethane for waterproofing and terraces, decks or covers/roofs.

We recommend to read its Technical Data Sheet carefully.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: ESTABLECIMIENTOS BAIXENS S.L.

Address: Pol. Industrial Moncarra, s/nº

City: 46230 - ALGINET
Province: VALENCIA
Telephone: 96 175 08 34
Fax: 96 175 93 92

E-mail: <u>laboratorio@baixens.com</u>
Web: <u>www.baixens.com</u>

1.4 Emergency telephone number: 961 750 834 (Only available during office hours; Monday-Friday; 08:00-18:00) Toxicological Information Service (National Institute of Toxicology and Forensic Science) Telephone: +34 91 5620420. Information in Spanish (24h/365 days). Intended with the only purpose of providing medical assistance in an emergency situation.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008: Skin Sens. 1: May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Warning

Hazard statements:

H317 May cause an allergic skin reaction.

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR

Version 1 Date of compilation: 05/06/2025

Revision date: 05/06/2025



Page 2 of 10

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P321 Specific treatment.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of the contentando/or its container as a hazardous waste, through an authorized waste management

company, in accordance with the current regulations.

EUH statements:

EUH208 Contains 2-methylisothiazol-3(2H)-one, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
Identifiers			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 13463-67-7 EC No: 236-675-5 Registration No: 01- 2119489379-17-XXXX	Titanium dioxide	0 – 3.5 %	-	-
Index No: 613-088- 00-6 CAS No: 2634-33-5 EC No: 220-120-9 Registration No: 01- 2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	0.06 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Skin Sens. 1, H317: C ≥ 0,05 %

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR



Revision date: 05/06/2025



Page 3 of 10

Index No: 613-326- 00-9 CAS No: 2682-20-4 EC No: 220-239-6 Registration No: 01- 2120764690-50-XXXX	2-methylisothiazol-3(2H)-one	0.06 %	Acute Tox. 2, H330 - Acute Tox. 3, H311 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 (M=1) - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317	Skin Sens. 1A, H317: C ≥ 0,0015 %
---	------------------------------	--------	---	---

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eve contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. If the person vomits, clear the respiratory tract. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.


Exposure to combustion or decomposition products can be harmful to your health.

^{*} See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

^[2] Substance with a national workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR



Revision date: 05/06/2025



Page 4 of 10

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Application of the product in the conditions and supports indicated in the FT of the same. Uses specified in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR

Version 1 Date of compilation: 05/06/2025

Revision date: 05/06/2025



Page 5 of 10

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %					
Uses:	Water-proofer					
Breathing protect	Breathing protection:					
If the recommended	If the recommended technical measures are observed, no individual protection equipment is necessary.					
Hand protection:						
PPE:	Work gloves.					
Characteristics:	«CE» marking, category I.					
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420					
	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible.					
Maintenance:	Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or					
	adhesives.					
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.					
	Always use with clean, dry hands.					
Material:	PVC (polyvinyl chloride) Breakthrough time A80 Material thickness O,35					
Evo protoctions	(mm): 0,33					
	Eye protection: If the product is handled correctly, no individual protection equipment is necessary.					
Skin protection:	idied correctly, no individual protection equipment is necessary.					
PPF:	Protective clothing.					
=-	«CE» marking, category II. Protective clothing should not be too tight or loose in					
Characteristics:	order not to obstruct the user's movements.					
CEN standards:	EN 340					
	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by					
Maintenance:	the manufacturer.					
	The protective clothing should offer a level of comfort in line with the level of protection provided in					
Observations:	terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level					
	of activity and the expected time of use.					
PPE:	Work footwear.					
Characteristics:	«CE» marking, category II.					
CEN standards:	EN ISO 13287, EN 20347					
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.					
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident					

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid Colour: Characteristic

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: > 60 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: 86.5-8.5

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: Not applicable/Not available due to the nature/properties of the product Liposolubility: Not applicable/Not available due to the nature/properties of the product

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR



Revision date: 05/06/2025



Page 6 of 10

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product

Vapour pressure: Not applicable/Not available due to the nature/properties of the product Absolute density: Not applicable/Not available due to the nature/properties of the product

Relative density: 1.29±0.07 gr/cm3

Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: 40000-60000 cP (A/6/10)

Explosive properties: Not applicable/Not available due to the nature/properties of the product Oxidizing properties: Not applicable/Not available due to the nature/properties of the product Dropping point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

Solids content: 54-59%

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

Toxicological information about the substances present in the composition.

Name	Acute toxicity				
Name	Туре	Test	est Kind Value		
		LD50 Rat 1020 mg/kg bw [1		1020 mg/kg bw [1]	
1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	Oral	[1] Pharmacological Research Communications. Vol. 3, Pg. 385, 1971			
Del izisoti ilazoiii 1-5-oi le	Dermal				
CAS No: 2634-33-5	Inhalation				

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR

Version 1 Date of compilation: 05/06/2025

Revision date: 05/06/2025



Page 7 of 10

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
Name	Туре	Test	Kind	Value
1,2-benzisothiazol-3(2H)-one,1,2-benzisothiazolin-3-one	Fish	LC50 Fish 10 mg/l (96 h) [1] [1] Linden, E., B.E. Bengtsson, O. Svanberg, and G. Sundstrom 1979. The Acute Toxicity of 78 Chemicals and Pesticide Formulations Against Two Brackish Water Organisms, the Bleak (Alburnus alburnus) and the Harpacticoid Nitocra spinipes. Chemosphere 8(11/12):843- 851 (Author Communication Used) (OECDG Data File)		
Denzisounazoiin-3-one	Aquatic invertebrates	EC50 Crustacean 4,4 mg/l (48 h) [1] [1] Office of Pesticide Programs 2000. Pesticide Ecotoxicity Database (Formerly: Environmental Effects Database (EEDB)). Environmental Fate and Effects Division, U.S.EPA, Washington, D.C		
CAS No: 2634-33-5 EC No: 220-120-9	Aquatic plants			

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present.


No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR



Revision date: 05/06/2025



Page 8 of 10

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport. IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR

Version 1 Date of compilation: 05/06/2025

Revision date: 05/06/2025



Page 9 of 10

Volatile organic compound (VOC)

Product subcategory: one-pack performance coating, water-borne

Phase I* (from 1.1.2007): **140** Phase II* (from 1.1.2010): **140**

* g/l ready to use

VOC content (g/l): <140 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 2: Acute toxicity (Inhalation), Category 2
Acute Tox. 3: Acute toxicity (Dermal), Category 3
Acute Tox. 3: Acute toxicity (Oral), Category 3
Acute Tox. 4: Acute toxicity (Oral), Category 4

Acute Tox. 4: Acute toxicity (Oral), Category 4 Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1

Eye Dam. 1 : Serious eye damage, Category 1 Skin Corr. 1B : Skin Corrosive, Category 1B Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1A : Skin sensitiser, Category 1A

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

(in accordance with Regulation (EU) 2020/878)

ACRILASTIC PUR

Version 1 Date of compilation: 05/06/2025

Revision date: 05/06/2025



Page 10 of 10

Abbreviations and acronyms used:

CEN: European Committee for Standardization.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.