



Plaster for filling and smoothing surfaces with small flaws on gypsum or cement substrates

Plastering, smoothing and filling

in works where a thin layer application is required, filling holes, cracks, micro-fissures, depressions...

Easy sanding

Its structured formulation and the incorporation of cutting-edge additives make it an easy sanding product.



Available in formats of: 1 – 5 - 15 Kg

CLASSIFICATION ACCORDING TO STANDARD

UNE-EN 16566

G3S2V3W2A0C0R0



PROPERTIES AND USES

- Standard setting.
- Easy to apply, smooth and sand.
- Thin layer applicable.
- Filling of small holes, fissures and non-movement cracks.
- Smoothing of walls with flaws (scratches, lines, dents...)
- Recommended storage time: 12 months inside its original packing.
- Use: Gypsum, cement, traditional synthetic paint. Surfaces must be free of flaws, dry, cohesive, absorbent, and well adhered. It can be coated by all types of conventional paints after complete drying.



Water for mixing

0.40 to 0.45 litres water per kg of plaster



Performance in layer of 1mm

1.10 Kg/m²



6.0 - 7.0



Maximum thickness per layer

1 mm



Adhesion

>0,7 MPa on cement and paint



Fire classification

A1



Useful life

4 – 5 Hrs.



Drying time in 1mm thickness

Concrete and paint: 4 – 6 Hrs.
Plaster: 3 -4 Hrs.



Granulometry

300 Microns