



Ready to use flexible micro-fibred putty for plastering tiles and exterior substrates.

## Smoothing, repairing

On gypsum, plaster, cement, tile substrates and in all kinds of exterior surfaces.

## Ceramic covering

Specially designed for applying on plaster and ceramic bases.

Can be used as tile flashing.

Ideal as an exterior putty.



Available in formats of : 1 – 5 - 15 Kg

CLASSIFICATION ACCORDING TO STANDARD  
UNE-EN 16566

**G<sub>3</sub>S<sub>2</sub>V<sub>2</sub>W<sub>2</sub>A<sub>0</sub>C<sub>0</sub>R<sub>0</sub>**



### PROPERTIES AND USES

- Micro-fibred.
- Extra white.
- Excellent thixotropy.
- Easy to apply and sand.
- Recommended Storage Time: 12 months inside its original packing.
- Use: Gypsum, plaster, cement, brick, stone, wood, concrete, aerated concrete, semi-absorbent substrates, conventional synthetic paint, enamel, tiles, ceramic. Surfaces must be free of flaws, dry, cohesive, absorbent, and well adhered.
- Can be coated by all types of conventional paints after complete drying.
- INFORMATION OF STANDARD 2004/42/CE: CATEGORY II, HIGH PERFORMANCE WATER-BASED SINGLE COMPONENT COATINGS. Limit: 140g/l COV (2007); 140g/l COV (2010). This product contains 1,29 g/l COV max.



**Preparation**  
Ready to use  
Clean tools with water



**Performance in layer of 1mm**  
1.50 Kg/m<sup>2</sup>



8.0 - 9.0



**Maximum thickness per layer**  
2 mm



**Adhesion**  
> 15.0 Kg/cm<sup>2</sup> on cement  
> 13.0 Kg/cm<sup>2</sup> on cement



**Fire classification**  
A2 - s1 - d0



**Useful life**  
Unlimited



**Drying time in 1mm thickness**  
Concrete: 6 - 7 H.



**Maximum Granulometry**  
200 Microns