


RX-105

Rualaix®

3F'XPERT

Plaster for indoor/interior renovating, smoothing and levelling.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR



COATED

BY ALL KINDS OF CONVENTIONAL NON- RESILIENT
PAINTS AFTER COMPLETE DRYING

CLASSIFICATION ACCORDING TO
UNE 48313: 2008 EX

G3S2V3W2A0C0R0

USE

Gypsum, plaster, cement, concrete, bricks, laminated stipple, non-elastic synthetic paint. Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Medium setting.
- Multilayer applicable fresh on fresh.
- Contains micronized microspheres.
- Thick or thin layer applicable.
- Possibility of using airless blaster if used before setting time and useful life of product.
- Easy to apply, smooth and sand.
- Non-repellent.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Renovating, filling and levelling of rough or textured surfaces improving presentation of the surface treated.
- Smoothing of stipple walls.
- Renovating of painted walls.
- Sealing of non-movement imperfections and fissures.



Pallet of 66 sacks
x 15 Kgs.



Pallet of 35 cases
of 4 x 5 Kgs



Pallet of 36 cases of
20 x 1 Kg.



PREPARATION

0.45 litres of water per Kg. of plaster



PERFORMANCE

1.15 Kg/m²/mm



7.0-8.0



MAXIMUM THICKNESS PER COAT

7 mm



ADHESION

>13kg/cm² on cement
>6kg/cm² on paint



FIRE RESISTANCE CLASSIFICATION

A1



USEFUL LIFE

2 – 3 Hrs.



DRYING TIME IN 1mm THICKNESS

Plaster: 2 – 3 hrs.



MAXIMUM GRADING

200 microns