


RX-110E

Rualaix®

EXPRESS

Plaster suitable for filling, smoothing and renovating all types of substrates.
Quick dry.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR



COATED

BY ALL KINDS OF CONVENTIONAL NON- RESILIENT PAINTS AFTER COMPLETE DRYING

CLASSIFICATION ACCORDING TO
UNE 48313: 2008 EX

G3S2V3W2A0C0R0

USE

Gypsum, plaster, cement, concrete, brick walls, stone, tiles, non-elastic synthetic paint, glass paste, low absorption bases.
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Quick setting.
- Quick drying.
- Easy to apply.
- Thick or thin layer applicable.
- Maximum grip even on low absorption surfaces.
- High resistant finish.
- Easy to sand.
- Brilliant white colour.
- Storage: 6 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Renovating and covering cracks and flaws.
- All types of quick repairs.



15Kg Pallet of 66 sacks x 15 Kgs.

5Kg Pallet of 35 cases of 4 x 5 Kgs

1Kg Pallet of 36 cases of 20 x 1 Kg.

PREPARATION
0.40 - 0.45 litres of water per Kg. of plaster

PERFORMANCE
0.90 - 1.05 Kg/m²/mm

pH 7.0-8.0

MAXIMUM THICKNESS PER COAT
10 mm for plastering
Unlimited for covering

MPa ADHESION
>10kg/cm² on cement

FIRE RESISTANCE CLASSIFICATION
A2 - s1 - d0

USEFUL LIFE
30' - 50' Mins.

DRYING TIME IN 1mm THICKNESS
Concrete and paint: 3 - 4 hrs.
Plaster: 2 hrs. approx.

MAXIMUM GRADING
300 microns