

RX-111

Rualaix®

## RUSTIC PLASTER IN POWDER

Decorative coating for obtaining a rustic finish on walls.



INDOOR



### RECOATING

BY FINISHING WAX RX-502 CERLAIX

CLASSIFICATION ACCORDING TO  
EN 16566

**G3S2V3W2A0C0R0**

### USE

Gypsum, plaster, plasterboard sheets, cement, non-elastic synthetic paint.  
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES

- Slow setting.
- No sanding needed.
- Easy "one step" application.
- Smooth touch finish.
- Absence of splices.
- Possibility of covering gaps and small holes.
- Possibility of retouching shapes created before it starts to set.
- Storage: 12 months inside its original packing and kept free from damp and humidity.



15Kg

Pallet of 66 sacks  
x 15 Kgs.

### IDEAL FOR

- Obtaining walls with a rustic finish, old-fashioned walls or imitation of mud.



#### PREPARATION

0.65 litres of water per Kg. of plaster



#### PERFORMANCE

1.37 – 1.47 Kg/m2/mm



8.0-9.0



#### MAXIMUM THICKNESS PER COAT

2 mm



#### ADHESION

>6kg/cm2 on cement



#### FIRE RESISTANCE CLASSIFICATION

A2 – s1 – d0



#### USEFUL LIFE

>8 Hrs



#### DRYING TIME IN 1mm THICKNESS

Plaster and paint: 5 – 6 Hrs.



#### MAXIMUM GRADING

400 microns