


RX-112

Rualaix®

## STANDARD

Plaster suitable for recoating and smoothing walls with small flaws.  
Medium setting



\* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR



## COATED

BY ALL KINDS OF CONVENTIONAL NON- RESILIENT  
PAINTS AFTER COMPLETE DRYING

CLASSIFICATION ACCORDING TO  
UNE 48313: 2008 EX

G3S2V3W2A0C0R0

## USE

Gypsum, plaster, cement and non-elastic synthetic paint.  
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

## FEATURES

- Slow setting.
- Easy to apply, smooth and sand.
- Non-repellent.
- Applicable in thin layers.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

## IDEAL FOR

- Recoating small fissures or micro-fissures.
- Recoating non-movement and non-structural feature cracks.
- Smoothing and plastering large surfaces.



Pallet of 66 sacks  
x 15 Kgs.



Pallet of 35 cases  
of 4 x 5 Kgs



Pallet of 36 cases of  
20 x 1 Kg.



## PREPARATION

0.43 - 0.48 litres of water per Kg. of plaster



## PERFORMANCE

1.58 - 1.64 Kg/m2/mm



6.0-7.0



## MAXIMUM THICKNESS PER COAT

1 mm



## ADHESION

>0,7 MPa on cement and paint



## FIRE RESISTANCE CLASSIFICATION

A1



## USEFUL LIFE

8 Hrs. approx.



## DRYING TIME

Concrete and paint: 4 - 6 Hrs.  
Plaster: > 7 Hrs.



## MAXIMUM GRADING

300 microns