


RX-113

Rualaix®

GREEN LABEL

Plaster suitable for thin layer covering of large surface areas.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).



RECOATING

BY ALL TYPES OF NON-ELASTIC SYNTHETIC PAINTS
ONCE COMPLETELY DRY

CLASSIFICATION ACCORDING TO
EN 16566

G3S2V3W2A0C0R0

USE

Gypsum, plaster, cement and non-elastic synthetic paint.
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Slow setting.
- Easy to apply, smooth and sand.
- Non-repellent.
- Applicable in thin layers.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Full smoothing of walls with small flaws.
- Recoating small fissures or micro-fissures.
- Covering renovating plasters.



Pallet of 66 sacks
x 15 Kgs.



Pallet of 35 cases
of 4 x 5 Kgs



Pallet of 36 cases of
20 x 1 Kg.



PREPARATION

0.45 - 0.50 litres of water per Kg. of plaster



PERFORMANCE

0.90 - 1.05 Kg/m²/mm



6.0 - 7.0



MAXIMUM THICKNESS PER COAT

1 mm



ADHESION

>7 Kg./cm² on cement and paint



FIRE RESISTANCE CLASSIFICATION

A1



USEFUL LIFE

8 Hrs. approx.



DRYING TIME IN 1mm THICKNESS

Plaster: 3 Hrs. approx
Paint and concrete: 4 - 6 Hrs.



MAXIMUM GRADING

150 microns