


RX-114

Rualaix®

RED LABEL

Renovating plaster suitable for covering laminated stipple and renovating rough, punctured or embossed surfaces.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR



RECOATING

BY ALL TYPES OF NON-ELASTIC SYNTHETIC PAINTS
ONCE COMPLETELY DRY

CLASSIFICATION ACCORDING TO
EN 16566

G3S2V3W2A0C0R0

USE

Gypsum, plaster, plasterboard sheets, cement, non-elastic synthetic paint and laminated stipple.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Easy to apply, smooth and sand.
- Excellent covering power.
- Low superficial surface tension.
- Contains anti-cracking and surfactant agents.
- Single layer "fresh on fresh" applicable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Application of thick coats for covering flaws.
- Levelling of laminated stipple walls
- Renovating painted walls.
- Levelling of vertical surfaces.



Pallet of 66 sacks
x 15 Kgs.



Pallet of 35 cases
of 4 x 5 Kgs



PREPARATION

0.42 - 0.45 litres of water per Kg. of plaster



PERFORMANCE

0.90 - 1.05 Kg/m²/mm



6.5 - 7.5



MAXIMUM THICKNESS PER COAT

7 mm



ADHESION

>5 Kg./cm² on cement and paint



FIRE RESISTANCE CLASSIFICATION

A1



USEFUL LIFE

5- 7 Hrs.



DRYING TIME IN 1mm THICKNESS

Plaster: 3 - 4 Hrs.
Paint and concrete: 5 - 6 Hrs



MAXIMUM GRADING

300 microns