


RX-116

Rualaix®

BLUE LABEL

Plaster suitable for filling and re-covering cavities and cracks.  
Normal dry.



\* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR

**RE-COATING**

BY ALL TYPES OF NON-ELASTIC SYNTHETIC PAINTS  
ONCE COMPLETELY DRY

CLASSIFICATION ACCORDING TO REGULATION  
EN 16566

**G3S2V3W2A0C0R0**

**USE**

Gypsum, plaster, cement, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

**FEATURES**

- Quick setting.
- Normal drying.
- No cracking or shrinkage.
- Contains anti-cracking additives.
- Thick and thin layer applicable.
- Easy to sand.
- Easy to apply.
- Storage: 6 months inside its original packing and kept free from damp and humidity.

**IDEAL FOR**

- Covering sealing joints between sheets of plasterboard.
- Pasting moulds and decorative gypsum panels.
- Re-covering non-structural cracks and gaps.



15Kg Pallet of 66 sacks x  
15 Kgs.

5Kg Pallet of 35 cases  
of 4 x 5 Kgs.

1Kg Pallet of 36 cases  
of 20 x 1 Kg.

**WATER FOR MIXING**

0.45 - 0.50 litres of water per  
Kg. of plaster.

**PERFORMANCE**

0.90 – 1.05 Kg/m<sup>2</sup>/mm



6.0 - 7.0

**MAXIMUM THICKNESS PER COAT**

8 mm for plastering.  
Unlimited for covering

**ADHESION**

> 6 Kg./cm<sup>2</sup> on cement and paint

**FIRE RESISTANCE CLASSIFICATION**

A1

**USEFUL LIFE**

35' – 50' mins.

**DRYING TIME IN 1mm THICKNESS**

Paint and concrete: 4 - 5 Hrs  
Plaster: 3 - 4 Hrs.

**MAXIMUM GRANULOMETRY/GRADING**

200 microns