


RX-117

Rualaix®

PREMIUM GREEN LABEL

Smoothing plaster suitable for thin layer covering of large surface areas.
Excellent workability.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR



RE-COATING

BY ALL TYPES OF NON-ELASTIC SYNTHETIC PAINTS
ONCE COMPLETELY DRY

CLASSIFICATION ACCORDING TO REGULATION

EN 16566

G3S2V3W2A0C0R0

USE

Gypsum, plaster, cement, non-elastic synthetic paint.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Slow setting.
- Easy to apply, smooth and sand.
- Non-repellent.
- Smooth and fine finishes.
- Thin layer applicable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Covering small fissures and micro-fissures.
- Smoothing and plastering walls with small flaws.
- Coating renovation plasters.



15Kg

Pallet of 66 sacks x
15 Kgs.



WATER FOR MIXING

0.45 - 0.50 litres of water per
Kg. of plaster.



PERFORMANCE

0.90 – 1.05 Kg/m²/mm



6.0 - 7.0



MAXIMUM THICKNESS PER COAT

1 mm.



ADHESION

>10 Kg./cm² on cement and paint



FIRE RESISTANCE CLASSIFICATION

A1



USEFUL LIFE

Over 8 hrs.



DRYING TIME IN 1mm THICKNESS

Paint: 6 - 7 Hrs.
Plaster and concrete: 4 - 5 Hrs



MAXIMUM GRANULOMETRY/GRADING

200 microns