


RX-122

Rualaix®

## QUICK RED LABEL

Renovating plaster suitable for covering laminated stipple and smoothing of rough, punctured or embossed surfaces. Quick setting.



\* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).

INDOOR



### USE

Gypsum, plaster, non-elastic synthetic paint and laminated stipple. Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

### FEATURES

- Easy to apply, smooth and sand.
- Quick setting.
- Quick drying.
- Micro-fibered product.
- Medium surface tension product.
- Single layer "fresh on fresh" applicable.
- Excellent covering power.
- Contains anti-cracking and surfactant additives.
- Thick layer applicable.
- Storage: 6 months inside its original packing and kept free from damp and humidity.

### IDEAL FOR

- Quick levelling of laminated stipple walls.
- Quick renovating of painted walls.



### RE-COATING

BY ALL TYPES OF NON-ELASTIC SYNTHETIC PAINTS  
ONCE COMPLETELY DRY

CLASSIFICATION ACCORDING TO REGULATION  
EN 16566

**G3S2V3W2A0C0R0**



15Kg

Pallet of 66 sacks x  
15 Kgs.



#### WATER FOR MIXING

0.40 - 0.45 litres of water per  
Kg. of plaster.



#### PERFORMANCE

0.90 - 1.05 Kg/m<sup>2</sup>/mm



8.5 - 9.5



#### MAXIMUM THICKNESS PER COAT

10 mm



#### ADHESION

>5 Kg./cm<sup>2</sup> on cement and paint



#### FIRE RESISTANCE CLASSIFICATION

A2 - s1 - d0



#### USEFUL LIFE

40' - 70' mins



#### DRYING TIME IN 1mm THICKNESS

Absorbent: 2 Hrs. approx.  
Non-absorbent: 4 - 5 Hrs.



#### MAXIMUM GRANULOMETRY/GRADING

200 microns