

RX-127

Rualaix®

ISOLXTREM DE INTERIOR

Plaster in powder suitable for thermally and acoustically insulating interior areas.

INTERIOR



COATED

BY ALL TYPES OF NON-RESILIENT PAINTS
ONCE COMPLETELY DRY

CLASSIFICATION ACCORDING TO STANDARD

EN 16566

G3S2V3W3A0C0R0

USES

Conventional absorbents or semi-absorbent primers, gypsum, plasterboard, plaster, cement, concrete and non-elastic synthetic paint.

Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Easy to apply, smooth and sand.
- Formulated based on hollow microspheres.
- Excellent covering power.
- Lightened product. No cracks or shrinkage.
- Breathable to water vapour.
- Increases condensation point of interior substrates where it has been applied (report No.11/3716-2702).
- Anti-condensation.
- Sound insulation: Dampens outside noise and vice-versa.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Thermally and acoustically isolating rooms.
- Prevents the formation of condensation water in high humidity content areas.



9kg

Pallet of 66 sacks
of 9 Kg.



Water for mixing

0,44 – 0,48 litres of water per kg of plaster



Performance

0.6 - 0.8 Kg/m²/mm



7.0 - 8.0



Maximum thickness on application

20 mm



Adhesion

>5 Kg/cm² on cement
>3 Kg/cm² on paint



Fire classification

A1



Useful life

1 H: 45' - 2 H: 15'



Drying Time in 1mm thickness

Escayola: 2-3 H



Maximum Granulometry

200 micras