


RX-312

Rualaix®

GARN 'XPERT

Plaster for renovating (smoothing, filling and recoating).
Ready to use



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).



USE

Gypsum, plaster, painted bases, laminated stipple, fibreglass painted canvas, cement, cement mortars and any type of absorbent substrates and regular in construction. Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free from dust.

FEATURES

- Excellent workability.
- Non-repellent.
- Non-drip.
- Ready to use product.
- Easy to apply.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Renovating old or painted bases.
- Repairing of lines, bumps, scratches and micro-fissures.
- Levelling of embossed or textures bases.
- Smoothing laminated stipple.
- Filling joints between plasterboard sheets.



INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY I1, HIGH PERFORMANCE ONE COMPONENT
COATINGS, WATER-BASED

Limit: 140 g/l COV (2007); 140 g/l COV (2010)
This product contains 0,44 g/l COV max.

RECOATING

BY ALL TYPES OF NON-ELASTIC PAINTS, ONCE
COMPLETELY DRY
CLASSIFICATION ACCORDING TO REGULATION
NF T36-005: FAMILY III - CLASS 2

CODE (EN 16-565)

G3S2V2W2A0C0R0



20Kg	Pallet of 44 buckets of 20 Kg.	6kg	Pallet of 120 buckets of 6 Kg.
1Kg	Pallet of 44 cases of 12 x 1 Kg.		



Preparation

Ready to use.
Clean tools with water.



Performance

1.50 - 2.00 Kg/m²/mm



Maximum thickness per coat

3 mm



Adhesion

> 8 Kg/cm² on paint
> 7 Kg/cm² on concrete



8.5 - 9.5



Maximum granulometry/grading

200 microns



Useful life

Unlimited



Drying time in 1mm thickness

Absorbent substrate: 3 - 4 hrs.