

RX-402

Rualaix®

UNIVERSAL

Plaster suitable for smoothing and re-coating of all types of substrates.
Covers ceramics.



INFORMATION ON DIRECTIVE 2004/42/CE
CATEGORY II, HIGH PERFORMANCE ONE COMPONENT
COATINGS, WATER-BASED

Limit: 140 g/l COV (2007); 140 g/l COV (2010)
This product contains 6,10 g/l COV max.

RECOATING


BY ALL TYPES OF NON-ELASTIC PAINTS, ONCE
COMPLETELY DRY

CLASSIFICATION ACCORDING TO REGULATION

NF T36-005: FAMILY III - CLASS 2

CODE (EN 16-565)

G3S2V2W2A0C0R0



USE

Gypsum, plaster, cement, non-elastic synthetic paint, traditional varnishes, tiles.
Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Easy to apply and excellent workability.
- Slightly fibrous product.
- Easy to apply, smooth and sand
- Powerful grip.
- Thin layer applicable
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Plastering walls and façades with little or zero water absorption.



15Kg Pallet of 33 buckets
of 15 kg.

5Kg Pallet of 24 cases
of 4 x 5 kg.

1Kg Pallet of 44 cases
of 12 x 1 kg.



Preparation

Ready to use.
Clean tools with water.



Performance

1.45 - 1.55 Kg/m²/mm



Maximum thickness per coat

1 mm



Adhesion

> 13 Kg/cm² on paint
> 10 Kg/cm² on concrete



Useful life

Unlimited



Drying time in 1mm thickness

Tiles: 6 - 7 hrs.
Concrete: 5 - 6 hrs.



7.0 - 8.0



Fire resistance classification

D - s2 - d0



Maximum granulometry/grading

200 microns