


RX-409

RX-409C

Rualaix®

LEGNOSTUC

Fibre filler suitable for smoothing, recovering and sealing of wood



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY I, HIGH PERFORMANCE ONE COMPONENT
COATINGS WATER-BASED

LIMIT: 140G/L COV (2007); 140g/l COV(2010)
This product contains 3,60 g/l COV max.

COATED

BY ALL KINDS OF CONVENTIONAL NON- RESILIENT
PAINTS AFTER COMPLETE DRYING

CLASSIFICATION ACCORDING TO
STANDARD EN 16566

G3S2V2W2A0C0R0

USE

Natural wood, laminated flooring, parquet flooring, wooden frames, furniture. Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Excellent workability.
- Contains micronized natural fibres.
- Easy to smooth.
- Easy to sand.
- Excellent filling capacity.
- Firm adhesion
- Superficial film of extreme toughness
- 14 colour range.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Smoothing, recovering and sealing wooden surfaces.



Pallet of 96 boxes
of 8 x 200 g



Pallet of 96 boxes
of 4 x 500 g



Pallet of 64boxes
of 18 x 250 g



Pallet of 120 boxes
of 12 x 300g



PREPARATION

Ready to use. Clean tools with water



PERFORMANCE

1.45-1.65Kg/m2/mm



MAXIMUM THICKNESS PER COAT

10 mm



ADHESION

>9 Kg/cm2 on cement and paint



8.0 - 9.0



FIRE RESISTANCE CLASSIFICATION

A2 - s1 - d0



USEFUL LIFE

Unlimited



DRYING TIME

Absorbents: 3 - 4 hrs.



MAXIMUM GRADING

200 microns