


RX-413

Rualaix®

FILLER

Light weight fibered repairing plaster for filling imperfections and levelling of irregularities. Thick coat.


INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY i1, HIGH PERFORMANCE ONE COMPONENT COATINGS WATER-BASED

LIMIT: 140G/L COV (2007); 140g/l COV(2010)
This product contains 3,63g/l COV max.

COATED

BY ALL KINDS OF CONVENTIONAL NON- RESILIENT PAINTS AFTER COMPLETE DRYING

CLASSIFICATION ACCORDING TO
STANDARD EN 16566

G3S2V2W2A0C0R0

USE

Gypsum, plaster, cement, reinforced concrete, wood, polystyrene, furniture, doors, plasterboard, non-resilient plastic paint and absorbents in general. Surfaces should be free from flaws, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Excellent workability.
- Easy to smooth and sand.
- Minimum shrinkage.
- Excellent filling capacity.
- Firm adhesion, cohesion and hardness.
- Reinforced with fibre glass
- Paintable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Getting rid of flaws, gaps and cracks.
- Smoothing, repairing and sealing wooden surfaces.
- Levelling of irregular sub-layers
- Repairing decorative gypsum and polystyrene components.



Pallet de 24 boxes
of 4x5 kg



Pallet de 44 boxes
of 12 x 1 kg


PREPARATION

Ready to use. Clean tools with water


PERFORMANCE

1.45-1.65Kg/m2/mm



8.0 - 9.0


MAXIMUM THICKNESS PER COAT

10 mm


ADHESION

>9 Kg/cm2 on cement and paint


FIRE RESISTANCE CLASSIFICATION

A2 - s1 - d0


USEFUL LIFE

Unlimited


DRYING TIME

Absorbents: 3 - 4 hrs.


MAXIMUM GRADING

200 microns