


RX-417

ISOLXTREM®

PINTHERM

Matt paint suitable for isolating thermally, acoustically and anti-condensation.



## USES

RX-127 Rualaix Isolxtrem Interior, plaster, plasterboard, gypsum, cement, concrete, non-elastic synthetic paints, usual masonry (absorbent) substrates.

Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

## FEATURES

- Washable.
- Good cover.
- High performance.
- Increases condensation point to interior substrates where it has been applied (report No.11/3716-2702).
- Anti-condensation.
- Prevents the appearance of mold, algae and other micro-organisms on the substrates.
- Confers thermal insulation to the substrate.
- Provides a reduction in noise intensity.
- The system application of RX-417 on RX-127 provides an enhanced insulation system.
- Resistant to water and humidity.
- Breathable.
- Thermal insulation of hot and cold-water pipes.
- Reverberation noise reduction.
- Can be coloured.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

## IDEAL FOR

- Protecting walls where moisture is generated by condensation.
- Applying in facilities with high temperatures and humidity (restaurant kitchens, indoor swimming pools, saunas, bathrooms, spas...)

### INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY a1, MATT PRODUCTS FOR WALLS AND CEILINGS (SHINE <25 TO 60°), WATER-BASED.

Limit: 70g/l COV (2007); 30g/l COV (2010)  
This product contains: 4,80g/l COV max.



15l Pallet of 33  
buckets of 15 l.

4l Pallet of 120  
buckets of 4 l.

750ml Pallet of 44 cases  
of 12 x 750ml.



### Preparation

First coat: 5 – 10% with water.  
Do not dilute following coats.



### Performance

0,6-1 l/m<sup>2</sup>



8.0 - 10.0



Apply with brush, roller or airless.



### Cleaning of tools

Use water



Water-based



### Useful life

Sin Unlimited



### Drying Time to touch

10 – 20 minutes.