


RX-419C

CARTRIDGES

ACRYL'XPRT

Acrylic putty suitable for treating cracks and fissures.



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY i1, HIGH PERFORMANCE ONCE
COMPONENT WATER-BASED COATINGS

Limit: 140g/L COV (2007); 140g/l COV (2010)
This product contains: 1,24g/l COV max.

COATED

BY ALL TYPES OF CONVENTIONAL NON-RESILIENT
PAINTS AFTER COMPLETELY DRYING

USES

Gypsum, plaster, cement, brick, stone, wood, concrete, aerated concrete and semi-absorbent substrates. Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- White.
- Applicable in thickness.
- Excellent thixotropy.
- Flexible.
- Great adhesion.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Repairing cracks, fissures and micro-fissures between materials of different nature.



Pallet of 44 cases
of 24 x 310 ml



Preparation
Ready to use.



Performance in layer of 5 mm and 1 cm thickness
65 – 75 g/m lineal



7.0 - 9.0



Maximum thickness on application
Unlimited for covering



Adhesion
Initial: > 13 Kg/cm²
After thermal aging: > 29 Kg/cm²



Density
1,51 ± 0,07



Useful life
Unlimited



Drying Time to touch: 60' - 90'
Deep drying: 24 Hrs



Maximum Granulometry
< 50 microns