


RX-420

Rualaix®

MURALAIX PÂTE

Fibrous plaster for renovating and repairing façades, smooth and light finish.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A+ (very low emissions).



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY II, HIGH PERFORMANCE ONE COMPONENT

COATINGS, WATER-BASED

LIMIT: 140G/L COV (2007); 140g/l COV(2010)

This product contains 1,27g/l COV max.

RE-COATING

BY ALL TYPES OF CONVENTIONAL
PAINTS, ONCE COMPLETELY DRY.

CLASSIFICATION ACCORDING TO REGULATION

UE 48313: 2008 EX

G3E5S2V2AW2A0C0

USE

Gypsum, plaster, cement, concrete, wood, polystyrene, furniture, doors, tiles, plasterboard, non-elastic synthetic paint and any absorbent substrates in general.

Substrates must be healthy, dry, cohesive, absorbent, well adhered, clean and free from dust.

FEATURES

- Excellent workability.
- Easy to smooth and sand.
- Minimum shrinkage.
- Excellent filling capacity.
- Powerful grip, cohesion and hardness.
- Reinforces with fibre-glass.
- Quick dry.
- Brilliant white.
- Breathable.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Eliminating flaws, gaps and cracks.
- Levelling irregular substrates.
- Repairing decorative plaster and polystyrene elements.



Pallet of 45 sacks
of 15 kg.



Pallet of 24 cases of
4 x 5 Kg.



Pallet of 45 cases of
12 x 1 kg.



Pallet of 120 cases
of 12 x 300 g.



PREPARATION

Ready to use.
Clean tools with water.



PERFORMANCE

1.45 – 1.65Kg/m²/mm



MAXIMUM THICKNESS PER COAT

15 mm for plastering
Unlimited for re-coating



ADHESION

> 9Kg/cm² on cement and paint
> 6Kg/cm² on tiles



USEFUL LIFE

Unlimited



DRYING TIME IN 1mm THICKNESS

Absorbent: 3 - 4 hrs.



7.0 – 8.0



FIRE RESISTANCE CLASSIFICATION

A2- s1-d0 Flammable



MAXIMUM GRANULOMETRY/GRADING

200 microns.