


RX-502

Rualaix®

CERALAIX

Patina effect wax-based coating for high decoration.



* representative information on the emissions of volatile substances in indoor air that present a toxicological risk by inhalation on a scale from C (high emissions) to A + (very low emissions).

INDOOR



INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY II, HIGH PERFORMANCE ONE COMPONENT
COATINGS, WATER-BASED

LIMIT: 140g/l COV (2007); 140g/l COV(2010)
This product contains 0,20g/l COV max.

CLASSIFICATION ACCORDING TO REGULATION
EN 16566

G3S1V2W2A0C0R0

USE

RX-111 Rualaix Rustic Plaster in powder or RX_303 Rustic Plaster in paste.

FEATURES

- Gel texture.
- Washable.
- Smooth to the touch finishes.
- Matt finish.
- Storage: 12 months inside its original packing and kept free from damp and humidity

IDEAL FOR

- Obtaining rustic finished walls, old-fashioned and imitation mud walls.



1l

Pallet of 48 containers of 6
buckets of 1 liter



PREPARATION

Ready to use.
Clean tools with water.



PERFORMANCE

80-100 g/m²



7.0 – 8.0



Apply using brush, suede,
paint brush and sponge.



CLEANING OF TOOLS

Use water



FIRE RESISTANCE CLASSIFICATION

A2-s1-d0



OPEN TIME FOR EXTENDING WAX

30' – 45' mins.



DRYING TIME

1 hr. approx.



Water-based product.