

RX-519

Selladur®


SELLADUR FINISH

Fine finish water-proofer for Selladur treated substrates.



COATED

BY ALL TYPES OF NON-ELASTIC PAINTS ONCE COMPLETELY DRY.



USES

Selladur backgrounds.
Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

FEATURES

- Finishing product for a fine finish on Selladur treated substrates.
- Standard setting.
- Easy to apply.
- Permeable to water-vapour.
- Permeable to water.
- White colour product.
- Acts at positive or negative pressure.
- Product suitable for water-proofing drinking-water tanks according to requirements established in RD140/2003.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL PARA

- Leaving fine finishes in any waterproofing in the Selladur range of maximum granulometry.
- Control of humidity and the increase of resistivity for concrete structures according to UNE-EN 1504-2.
- Capillary humidity treatment.



15Kg Pallet of 33 buckets of 15 kg. **4Kg** Pallet of 35 boxes of 4 x 4 kg.



Water for mixing
0,26 litres of water per kg of powder.



Performance
1.0 - 1.5 Kg/m²/mm



12.0- 13.0



Maximum thickness on application:
2 mm



Adhesion
> 5 Kg/cm² on cement



Fire classification
A1



Useful life
1H30' - 2H30'



Drying Time in 2mm thickness
Concrete: 6 - 7 Hrs.



Maximum Granulometry
400 Microns