

# RX-523




## Preparation of surfaces

### CLEAN SAL

Saltpetre residue remover.



\* Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions).



### SURFACES

Application on usual surfaces used in construction (cement, concrete, brick, stone, ...).  
Do not apply on surfaces containing zinc or aluminium.

### CHARACTERISTICS

- Solution based on organic salts.
- Biodegradable.
- Non-smoking product.
- It has a very low odour level.
- Free of solvents, heavy metals and phosphates.
- Detergency properties that produce a streak-free surface.
- Cleaning and neutralization of saltpetre.
- Removal of alkaline saltpetre and efflorescence.
- Low corrosive effect on steel, copper, brass and bronze metal surfaces.



### IDEAL FOR

- Removal of saltpetre, efflorescence and cement splashes.

### ON-SITE APPLICATION

#### SURFACE PREPARATION

The surface must be sound, clean, dry, strong, well adhered, consistent and free of dust.

**RX-523****Preparation of surfaces****CLEAN SAL****ON-SITE APPLICATION****DIRECTIONS FOR USE**

A ready-to-use product. Do not dilute.

May be applied via a brush, roller, airless paint gun or an airbrush.

Corrosive products. Use appropriate personal protective equipment: gloves, safety goggles and face mask. Use in well ventilated areas.

Apply the product abundantly on the surface until it is saturated.

Leave to act for several seconds and then rub with a stiff (non-metallic) brush until all the particles that make up the efflorescence have been removed.

**TECHNICAL CHARACTERISTICS**

Density	1,20 ± 0.07 g/ml
pH	Approx. 1.0
Cleaning of tools	With water
Performance	3 - 4 m <sup>2</sup> /l

## INFORMATION ON DIRECTIVE 2004/42/CE – CATEGORY A

LIMIT COV	CONTENT COV
200 g/l (2007)	< 200 g/l maximum

**INFORMATION OF INTEREST**

The manufacturing process of our primers is controlled by batch, which allows traceability of any incident. The quality system used includes each article's design and production controls, both in terms of the raw materials used, guaranteeing uniform manufacturing, and the final item obtained. The use of ecotechnologies in our facilities' manufacturing processes allows for efficient work, without damaging the environment that surrounds us.

- Non-flammable product. Corrosive.
- Avoid the product coming into contact with skin and eyes.
- Smoking, eating and drinking must be prohibited in the application area.
- Comply with legislation on health and safety at work.
- Keep the product in a dry place, in original containers that are kept properly closed.
- Store the containers between 5°C and 35°C.
- Recommended storage time: 12 months from the date of manufacture in its original packaging and protected from moisture.

For further information on protective measures and first aid, please refer to the product's Safety Data Sheet.

RX-523



## Preparation of surfaces

## CLEAN SAL

## OBSERVATIONS

- For appropriate use and correct application of the product, it is essential to first read the technical data sheet.
- The data provided in this data sheet are for guidance only and should not be considered binding. The data has been obtained in normal laboratory conditions and on standardised surfaces, and can vary depending on the conditions in which the product is applied (surface absorption, applied thickness, temperature, environmental humidity, etc.). The ranges shown are based on logs of measurements. Slight deviations from the ranges presented in this technical sheet, whether higher or lower, will be accepted according to internal technical criteria and will not imply a loss of quality or affect the performance of the final product, due to (among other factors) variations in measurement conditions and any uncertainty associated with the instruments used.
- The working conditions of users are beyond our control.
- The product must not be used for purposes other than those specified. It is recommended that the instructions for use be strictly followed.
- It is essential that the state of the bases be assessed prior to each application.
- Do not mix with any material, as it will not retain its technical characteristics.
- Application temperature: from 5°C to 35°C.
- Do not apply on surfaces containing zinc or aluminium. Low corrosive effect on steel, copper, brass and bronze metal surfaces.
- The technical department of **ESTABLECIMIENTOS BAIXENS** hereby informs you that the designs of recently launched new products are considered to be in an experimental phase until an annual history can be constituted. From then on, the newly designed product is considered to be fully consolidated in the market. In the meantime, **BAIXENS** reserves the right to adapt its variable specifications or working ranges according to technical criteria. Any details subject to modification will be identified with an asterisk for easy identification; these may be recently created products and/or products in an experimental phase or improvements in our various ranges due to market needs and/or demands.
- We have a technical-commercial team at your disposal that can advise you with regard to any doubts or queries

## PACKAGING

FORMAT	5 l.	1 l.	750 ml.
UNIT/BOX	2	9	6
PALLETS	60 boxes	48 boxes	48 boxes



Internal code RX523NF1342A20