

RX-530

ISOLXTREM®

FIXATHERM

Thermal isolating systems, acoustic and anti-condensation fixer.



USES

Plaster, gypsumboard, gypsum, cement, concrete and absorbent masonry substrates. Ideal for RX-127 Rualaix Isolxtrem Interiors and RX-209 Rualaix Isolxtrem Exteriors and previous to applying RX-417 Rualaix Isolxtrem Pintherm. Surfaces must be sound, dry, cohesive, absorbent, well adhered, clean and free of dust.

INFORMATION ON DIRECTIVE 2004/42/CE

CATEGORY h1, WATER-BASED
CONSOLIDATING PRIMERS.

Limit: 50g/l COV (2007); 30g/l COV (2010)
This product contains: 1,98g/l COV max.

FEATURES

- Fixing and isolating product.
- Complementary to the Isolxtrem System.
- Confers thermal-insulating, deadening and anti-condensation properties.
- Prevents the presence of humidity on substrates.
- Insulating barrier in synergy with the components of the Isolxtrem System.
- Formula based on glass microspheres.
- Storage: 12 months inside its original packing and kept free from damp and humidity.

IDEAL FOR

- Fixing substrates treated with RX-127 and/or RX-209, improving its efficiency.
- Fixing substrates previous to applying RX-417.



Pallet of 2 cases
of 4 x 4 l.



Pallet of 44 cases
of 12 x 750ml.



Preparation

Ready to use. Possibility of diluting upto 5% in the first coat.



Performance

250 ml/m²



9.0 - 10.0



Application

Apply with brush, roller or airless.



Cleaning of tools

Use water



Fire Classification

E - d0



Useful life

Unlimited



Drying Time

Absorbents: 30 mins. approx



Water-based